

# MILLIE



The Millie LED downlight incorporating the Philips DLM Flex module and Xitaniumdriver for optimum performance. It is fitted with a 60°satin etched reflector and die cast twist and lock bezel for a range of interchangeable accessories.

40°specular and 50°multi-faceted reflectors are now available options. It offers a choice of colour temperatures, dimming and emergency conversion options. IP65 and decorative bezel options are also available.

## TECHNICAL FEATURES

- Equipped with Philips DLM Flex engines
- Die-cast aluminium twist and lock bezel
- Choice of 3000K or 4000K colour temperature
- Different output options up to 4550 lumens
- Maintained LED Emergency available in 3 options : Standard, Self Test and DALI Addressable
- Die Cast Aluminium With Aluminium Twist & Lock Bezel
- Open Fronted With Attachments Available
- White As Standard, Other Options Available

## MAINS OPERATION

Rated voltage supply: 220/240 V AC  
 Mains frequency: 50/60 Hz

## MECHANICAL

Bezel Diameter: 195mm  
 Cut-out Diameter: 176mm  
 Height: 132mm

## ORDER CODES

ORDER CODE	OUTPUT	POWER	COLOUR TEMPERATURE
EUME/1100/3K	1025 LM	9.5 W	3000K
EUME/1100/4K	1100 LM	9.5 W	4000K
EUME/1800/3K	1750 LM	17.5 W	3000K
EUME/1800/4K	1900 LM	17.5 W	4000K
EUME/2800/3K	2700 LM	30.5 W	3000K
EUME/2800/4K	2925 LM	30.5 W	4000K
EUME/4500/3K	4200 LM	46.5 W	3000K
EUME/4500/4K	4550 LM	46.5 W	4000K

## OPTIONS

- DALI Dimmable: /DA
- Chrome Bezel: /CH
- Brushed Aluminium Bezel: /BA
- IP65 Bezel: /IP65
- Integral Emergency: /E
- Self Test Emergency: /EST
- DALI Emergency: /EDA
- Clear glass halo: /CHALOGL
- Opal glass halo: /OHALOGL
- Frosted vertical halo: /FROSTVH
- Blue acrylic halo: /BLHALO

## DOWNLOADS

Product Datasheet



Photometric Download

