



The Azure is able to offer maximum flexibility with focus on low UGR to aid the LG7 compliance. It has wireless connectivity and a tuneable white. The Azure series is a winning choice for demanding office, commercial and educational applications

Features

Direct/indirect 600 x 600 LED
Modular
Micro prismatic central diffuser
Phillips LED and driver combination
Life up to >100,000h L70/B10
Low glare version for LG7 compliance
No Visible flicker (EEE 1789 - 2015)
Highly efficient ECA compliant versions
High output version 5125lm
Tridonic HCL tuneable white version
Wireless, dimming & emergency options

Dimensions

Length: 593mm
Width: 589mm
Height: 100mm

Order Codes

Order Code	Output	Power	Colour
EUAZ/32/830	2975LM	32W	3000K
EUAZ/32/840	3200LM	32W	4000K
EUAZ/31.5/830	3400LM	31.5W	3000K
EUAZ/31.5/840	3575LM	31.5W	4000K
EUAZ/46/830	4875LM	46W	3000K
EUAZ/46/840	5125LM	46W	4000K
EUAZ/52/TW	3875LM	52W	3000K - 6000K



Options

Digital addressable lighting interface:	/T+DALI
Casambi Wireless network (inc dim):	/BTC
EM conversion c/w integral indicator:	/EMI
DALI/self test EM c/w integral indicator:	/EMDI
Frame for plasterboard ceilings:	/PBF.184
Suspended mount body:	/SUS.184
Surface mount body:	/SURF.184
Wireless EasyAir:	/Contact Sales

Attachments

Digital addressable lighting interface:	/T+DALI
Casambi wireless network (inc dim):	/BTC
EM conversion c/c integral indicator:	/EMI
DALI/self test EM conversion c/w integral indicator:	/EMDI
Frame for plasterboard ceilings:	/PBF.184
Suspended mount body:	/SUS.184
Surface mount body:	/SURF.184
Tuneable white option:	/184.TW

