



The Azure series LED panel was developed to offer maximum flexibility with a focus on low UGR to aid LG7 compliance, wireless connectivity and tuneable white, The Azure Series is the perfect luminaire for demanding office, commercial and educational applications

### Features

- Direct / indirect 600 x 600mm LED modular
- Wipeable micro prismatic central diffuser
- Phillips LED and driver combination
- Life up to >100,000h L70/B10 with 5 year warranty
- Low glare version for LG7 compliance
- No visible flicker (IEEE 1789 - 2015)
- Highly efficient ECA compliant versions
- High output version 5125 Llm available
- Tridonic HCL tuneable white version available
- Wireless, dimming and emergency options available
- Can be used on plasterboard ceilings with accessory

### Dimensions

Length:	589mm
Width:	593mm
Height:	100mm

<u>Order code</u>	<u>Output</u>	<u>Power</u>	<u>Beam Angle</u>	<u>Colour Temperature</u>
EUAR/2975/830	2975 LM	33 W		3000K
EUAR/3200/840	3200 LM	36 W		4000K
EUAR/3400/830	3400 LM	38 W		3000K
EUAR/3575/840	3575 LM	40 W		4000K
EUAR/4875/830	4875 LM	55W		3000K
EUAR/5125/840	5125 LM	58W		4000K
EUAR/3875/830-840	3875 LM	44W		3000K – 6500K Tuneable White

### Options

Digital addressable lighting interface	/T+DALI
Casambi wireless network (inc dim)	/BTC
EM conversion c/w integral indicator	/EMI
DALI/ self test EM c/w integral indicator	/EMDI
Frame for plasterboard ceilings	/PBF.184
Suspended mount body	/SUS.184
Srface Mount Body	/SURF.184
Wireless EasyAir system	Contact Sales